STORMWATER MANAGEMENT REPORT

for:

HIGHLAND AVENUE SUBDIVISION

Block(s): 117 Lot(s): 93

Borough of Metuchen

Middlesex County, New Jersey

Prepared By:

Menlo Engineering Associates, Inc 261 Cleveland Avenue Highland Park, New Jersey 08904

T.: 732.846.8585 F.: 732.846.9439

Under the Immediate Supervision of:

William A Lane NJPE# 40262

BL/MAD/hc MEA # 2019.042 Dated: June 24, 2019

Revised: May 27, 2020 Revised: December 21, 2020 menlo engineering associates

O:\Documents\2019\2019.042\SWM\2019.042-Report-Stormwater Management (2020-12-21).doc

INTRODUCTION

The following Stormwater Management Report details the design of the stormwater management plan for a proposed subdivision located in the Borough of Metuchen, Middlesex County, New Jersey and has been prepared by Menlo Engineering Associates, Inc. in accordance with the standards of the Borough of Metuchen, the County of Middlesex, the New Jersey Soil Conservation Service, and the New Jersey Department of Environmental Protection. This report supplements, and should be reviewed in conjunction with, the project development plans prepared by Menlo Engineering Associates, Inc.

It is the intent of this report to aid and assist Engineers at the Municipal, County, and State levels in evaluating the drainage calculations and considerations incorporated in the design as shown on the plans submitted. This office will readily respond to questions and requests for additional calculations or verification of the proposed design by Municipal, County, or State Engineers, and will be responsive to their suggestions and modifications to the design in conformance to the applicable codes in the interest of land use control consistent with environmental protection.

STORMWATER MANAGEMENT PLAN & DESIGN

The guidelines for hydraulic design, as prepared by the Soil Conservation District, the Borough of Metuchen, Middlesex County and the New Jersey Department of Environmental Protection have been utilized for the drainage design of this project. The purpose of the drainage design is to safely conveyance the stormwater runoff and attenuate the discharges in accordance with the regulations promulgated by the above cited agencies.

The stormwater management plan for the site is to provide for conveyance of stormwater runoff from the proposed single-family dwellings and driveways to a stormwater collection system. The stormwater collection system will consist of inlets and reinforced concrete pipe. The stormwater conveyance system has been designed for the 25-year storm and the inlet grates have been designed to comply with most current regulations.

The site is depicted by the Middlesex County Soil Manual Boonton-Urban Land (BouB). Per the Soil Conservation Urban Hydrology for Small Watersheds, Boonton-Urban Land has a high runoff potential. "C" Classifications have conservatively been used in runoff computations.

The proposed subdivision does not result in a net increase in impervious coverage of more than 0.25 acres nor propose more than 1.0 acres of disturbance. Therefore, the stormwater management regulations are not triggered, and stormwater management is not required.

CONCLUSION

The proposed stormwater management system for the proposed subdivision has been designed with provisions for safe and efficient control of stormwater runoff in a manner which will not adversely affect the existing drainage patterns found in the surrounding areas. It is the opinion of this office that the proposed development will not have any negative impacts on the drainage characteristics of the site, or the immediately surrounding areas. Further, it is the opinion of this office, that the proposed development will be in compliance with all applicable stormwater management regulations as established by the NJDEP and Borough of Metuchen Standards.

APPENDIX A: EXISTING CONDITIONS

PRE-DEVELOPMENT DRAINAGE CONDITION

I. Total Drainage Area:

1.11 Acres

II. Soil Groups/Types:

BouB -Boonton-Urban Land

Type C

III. Time of Concentration:

10 Minutes

IV Rainfall Intensity:

<u>Storm</u>	Rainfall(in.)
100-YR	8.00
25-YR	6.70
10-YR	5.80
2-YR	4.20
1-YR	3.20

V. Weighted 'c' Calulation:

Land Use	<u>Area</u>	% of Cover	C Value	<u>Total</u>
Impervious	0.08 Acres	0.07	0.99	0.07
Gravel	0.15 Acres	0.14	0.84	0.11
Grass	0.88 Acres	0.79	0.51	0.40
Woods	0.00 Acres	0.00	0.45	0.00
			Weighted 'c':	0.58

VI. Q=ciA

Q=	<u>c</u>	<u> </u>	<u>A</u>	=	Q	_
$Q_{100} =$	0.58	8.00	1.11	=	5.2	
Q ₂₅ =	0.58	6.70	1.11	=	4.3	
Q ₁₀ =	0.58	5.80	1.11	=	3.7	
$Q_2 =$	0.58	4.20	1.11	=	2.7	

APPENDIX B: PROPOSED CONDITIONS

POST DEVELOPMENT RUNOFF CONDITION

I. Total Drainage Area:

1.11 Acres

II. Soil Groups/Types:

BouB -Boonton-Urban Land

Type C

III. Time of Concentration:

10 Minutes

IV Rainfall Intensity:

<u>Storm</u>	Rainfall(in.)
100-YR	8.00
25-YR	6.70
10-YR	5.80
2-YR	4.20
1-YR	3.20

V. Weighted 'c' Calulation:

Land Use	<u>Area</u>	% of Cover	C Value	Total
Impervious	0.21 Acres	0.19	0.99	0.19
Gravel	0.14 Acres	0.13	0.84	0.11
Grass	0.76 Acres	0.68	0.51	0.35
Woods	0.00 Acres	0.00	0.45	0.00
			Weighted 'c'	0.65

VI. Q=ciA

Q=	<u>C</u>	1	<u>A</u>	=	Q	
$Q_{100} =$	0.65	8.00	1.11	=	5.8	
Q ₂₅ =	0.65	6.70	1.11	=	4.8	
$Q_{10} =$	0.65	5.80	1.11	=	4.2	
$Q_2 =$	0.65	4.20	1.11	=	3.0	

APPENDIX C: PIPE CALCULATIONS

Date: 6/5/2019 Hydraflow Storm Sewers Extension for Autodesk® Civil 3D® Plan Number of lines: 1 Project File: 2019.042-LINE A.stm

Storm Sewers v2019.20

Pipe Calc

1				
Line Dring Runoff Inlet 1				
Line Dring Runoff Inter 1 Inter	n-val Pipe		0.013	
Line Drng Runoff Inlet I Incr Total To Sys Runoff Capac Full State State Full Sys Runoff Capac C	Invert	(#)	101.27	
Line Dring Runorff Initer Initer Ca Area To ali To ali Critown Flow Cages Line Line Line Cages Cas	Invert	(£)	101.50	5/2019
Line Dring Runoff Inite Inite Cas Area Total Total Chrown Flow Capac Line Line Line Line Cas Cos Cas		(£/,£)	3.46)ate: 6/5
Line Dmg Runoff Inlet Inlet Q Area Total To Sys Runoff Q Repert Full (ft) (ac) (c) (min) (inhn) (cfs) (ac) (min) (inhn) (cfs)	Line	(%)	0.51	
Line Drng Runoff Injet 1 Incr Total TC Sys Runoff Qu Rabon Flow Length Area Coeff Time Injet Qu Area Sys Runoff Qu Rabon Gris Gri	Line	(in)	2	
Line Dring Runoff Time inlet a Area Coeff Time in Area Coeff	Capac	(cfs)	2.54	-
Line Dring Runoff Time inlet a Area Coeff Time in Area Coeff		(cfs)	1.57	r of lines:
Line Drng Runoff Inlet i Incr Total TC Sys Runoff (th) (ac) (CO) (min) (in/hr) (cfs) (ac) (min) (in/hr) (cfs) (ac) (min) (in/hr) (cfs) (ac) (min) (in/hr) (cfs) (ac) (ac) (ac) (ac) (ac) (ac) (ac) (ac	Known	(cfs)	00:0	Numbe
Line Drng Runoff Inlet inlet Q Area Sys (ft) (ac) (C) (min) (in/hr) (cfs) (ac) (min) (in/hr) (ac) 0.37 0.63 10.0 6.73 1.57 0.37 10.0 6.73 (in/hr) (in/	Total		1.57	
Line Drng Runoff Inlet i Incr Total (ft) (ac) (C) (min) (in/hr) (cfs) (ac) 45.106 0.37 0.63 10.0 6.73 1.57 0.37		(in/hr)	6.73	
Line Drng Runoff Inlet i Incr Length Area Coeff Time Inlet Q (ft) (ac) (C) (min) (in/hr) (cfs) 45.106 0.37 0.63 10.0 6.73 1.57		(min)	0.0	
Line Drng Runoff Inlet i Length Area Coeff Time Inlet (ft) (ac) (C) (min) (in/hr) 45.106 0.37 0.63 10.0 6.73	Total Area	(ac)	0.37	
Line Drng Runoff Inlet Coeff Time (ft) (ac) (C) (min) 45.106 0.37 0.63 10.0	a finct		1.57	
Line Drng Runoff (ft) (ac) (C) 45.106 0.37 0.63		(in/hr)		
Line Drng Length Area (ft) (ac) 45.106 0.37		(min)		
Line (ft) (ft) 45.106	Runoff	<u>(</u>)	0.63	
		(ac)	0.37	
Line Inlet Line Gnd/Rim No. ID EI Up (ft) (ft) 1 A2 P1 104.00	Line	(£	45.106	
Line Inlet Line 10 ID ID 11 A2 P1 Project File: 2019.042-L	Gnd/Rim El Up	£	104.00	INE A.stm
No. ID 1 A2 Project File: 201	Eii D		2	19.042-L
Project	Inlet		A2	File: 20'
	Line No.		~	Project

NOTES: Intensity = 42.39 / (Inlet time + 5.10) ^ 0.68 -- Return period = 25 Yrs.; ** Critical depth

Storm Sewers